

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 December 2000 (07.12.2000)


PCT

(10) International Publication Number
WO 00/72697 A1

- (51) International Patent Classification⁷: A23G 9/16, 9/04, 9/22, 9/28
- (21) International Application Number: PCT/EP00/04724
- (22) International Filing Date: 17 May 2000 (17.05.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
9912629.4 28 May 1999 (28.05.1999) GB
- (71) Applicant (for AE, AU, BB, CA, CY, GB, GD, GH, GM, IE, IL, KE, LC, LK, LS, MN, MW, NZ, SD, SG, SL, SZ, TT, TZ, UG, ZA, ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).
- (71) Applicant (for all designated States except AE, AU, BB, CA, CY, GB, GD, GH, GM, IE, IL, IN, KE, LC, LK, LS, MN, MW, NZ, SD, SG, SL, SZ, TT, TZ, UG, ZA, ZW): UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).
- (71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).
- (72) Inventors: BAKKER, Bastiaan, Hendrik; Unilever Research Vlaardingen, Olivier van Noortlaan 120, NL-3133 AT Vlaardingen (NL). BONGERS, Peterus, Martinus, Maria; Unilever Research Colworth, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB). WANG-NOLAN, Wei; Unilever Research Colworth, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).

[Continued on next page]

(54) Title: PROCESS AND APPARATUS FOR PRODUCTION OF A FROZEN FOOD PRODUCT



(57) Abstract: The performance of an extruder when used in the manufacturing of ice cream by operating with a pitch angle of between 28 and 45 degrees with screws which have more than one thread start.



WO 00/72697 A1



(74) **Agent:** HUGOT, Alain, Eric, Philippe; Unilever plc, Patent Department, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).

(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(81) **Designated States (national):** AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- 1 -

Process and apparatus for production of a frozen food
product

5 Technical field of the invention

The present invention relates to a process and an apparatus for the production of a frozen food product and more particularly an ice cream.

10

Background of the invention

Screw extruders such as single and twin screw extruders have been widely used and for a long time in the food industry, for example in the production of cereal based products. More recently, it has also been proposed to use single or twin screw extruders in the freezing of ice cream.

EP713650 discloses a process and an apparatus for extruding aerated frozen products wherein a twin screw extruder is used. The characteristic of the screws in the extruder is that they have a length over diameter ratio of between 30 and 60. It is not disclosed whether the diameter which is referred to is the diameter of the core of the screw or the diameter of the core of the screw plus its pitch. EP0808577 discloses a similar process and apparatus but whilst uses a single screw extruder having the same geometry.

EP561118 discloses a process and an apparatus for manufacturing frozen edible foams such as ice cream wherein a twin screw extruder is used. The geometry of the screw is defined by a (channel depth/channel width) ratio of approximately 0.1 and a pitch angle of between 22 and 30 degrees.

35

- 2 -

WO97/26800 discloses a process and an apparatus for manufacturing frozen edible foams such as ice cream wherein a single screw extruder is used. The geometry of the screw is defined by a (length of the screw/ inner diameter of the extruder barrel) ratio of between 5 and 10 a (pitch/external screw diameter) ratio of 1 to 2 and a (external diameter of the screw/inner diameter of the screw) of 1.1 to 1.4. According to the drawings, the screw has a single thread start.

10

One of the big problems faced when using an extruder for the manufacture of ice cream is that a temperature as low as possible is required while keeping an acceptable flow. Now, the lower the temperature the bigger the flow resistance which by generating frictions re-heats the product which is being cooled and limits the temperature which is thus achieved. There is therefore a need for optimising the geometry of the extruder in such a way that the increase in friction which is generated when the product is cooled is minimised in order to reach a temperature as low as possible.

15
20

It has now been found that it is possible to dramatically increase the performance of an extruder when used in the manufacturing of ice cream by;

25

- . operating with a pitch angle which is outside what has been used up to now in the manufacturing of ice cream,
- . operating with screws which have more than one thread start whereas up to now screws with only one thread start screws have been disclosed,
- . operating with extruders which are much shorter than what has been used up to now.

30

35

Tests and Definitions1. Screw parameters

- 5 An extruder screw is defined by different parameters which need accurate definitions. In order to help in the definition of such parameters, reference is made to Fig.1 which discloses a typical screw fitted in a single screw extruder. Such an extruder is, for example, described in
10 Engineering principles of plasticating extrusion - Zehev Tadmor - Krieger Publishing Company - 1978 - pages 39 to 45.

Screw length : LT (length of the screw which is in contact with the barrel)

15

Pitch length: Sp (axial distance of a full turn (screw lead))

- Thread starts: A screw can have more than one helix, in the
20 rest of the description, each helix is called a thread start and the number of thread starts is 'n'. On Fig.1, the screw which is represented has two thread starts.

- Channel depth: H (the distance between the root of the screw
25 and the inner surface of the barrel less the radial clearance between the crest of the screw and the inner surface of the barrel)

- Screw diameter De: Diameter of the barrel less the distance
30 between the root of the screw and the inner surface of the barrel.

Pitch angle: $\text{Arctg}(Sp/\pi \cdot De)$

- 4 -

Channel width: w_c (distance between the flights along a helical line which is perpendicular to the flight).

Summary of the invention

5

It is a first object of the present invention to provide an extruder comprising an extruding screw characterised by between 2 and 6 thread starts, preferably 2 and 5 thread starts, and a pitch angle of between 28 and 45 degrees,
10 preferably between 32 and 42 degrees.

Preferably the extruder comprises cooling means, more preferably, the cooling means are constituted by a cooling circuit wherein a cooling liquid is circulated. Even more
15 preferably the cooling liquid is ammonia or nitrogen.

It has been found that the higher the number of thread starts, the higher the ammonia temperature required to achieve a given temperature at the output of the extruder,
20 showing that increasing the number of thread starts leads to a better cooling effect.

Preferably the (H/w_c) ratio is between is less than 0.2, more preferably more than 0.1. It has been found that at low
25 H/w_c ratio, the heat exchange (cooling) improves but the thermal dissipation (heating) due to friction increases. Conversely at higher H/w_c ratio, the heat exchange decreases but the thermal dissipation decreases even more, therefore, operating at high H/w_c ratio is preferred. There is
30 nevertheless a limit in the H/w_c ratio which can be used since, above a certain limit, the product is no longer thermally homogeneous and cold and warm zones start appearing which do not mix any more.

- 5 -

Preferably also, the screw comprises between 3 and 4 thread starts and the cooling liquid is ammonia.

Preferably also the screw has a LT/De ratio of between 2 and 10, more preferably between 2 and 5, even more preferably between 2 and 4. It has been found that, and contrary to what is suggested by the prior art, not only there is no need for going for long screws but it is effectively a waste of energy. If the screw is too long, the heat dissipation due to the friction caused by the increase in viscosity generated by the cooling tends to equate the cooling effect and the two phenomenon (cooling and heat dissipation) equilibrate and there is no cooling taking place at the end of the screw. Nevertheless, the friction existing at the end of the screw, where no cooling takes place, requires additional torque to keep the screw rotating for no benefit to the process or the end product.

Preferably also, the extruder is a single screw extruder.

It is a second object of the invention to provide extruder comprising an extruding screw characterised by a pitch angle of between 28 and 45 degree, preferably between 32 and 42, and a LT/De ratio of between 2 and 10, preferably 2 and 5, more preferably 2 and 4.

It is a third object of the present invention to provide a process for the manufacturing of frozen food product, wherein a food composition is mixed, aerated and cooled down to a temperature of between -4°C and -7°C and then processed in an extruder for further cooling down to a temperature of between -12° and -20°, characterised in that the extruder comprises an extruding screw having 2 to 5 thread starts and a pitch angle of between 28 and 45 degrees, preferably between 32 and 42 degrees, and further comprises cooling

- 6 -

means, the cooling means being preferably constituted by a cooling circuit wherein a cooling liquid is circulated.

Preferably the cooling liquid is selected within the group
5 consisting of ammonia or nitrogen. More preferably, the screw comprises between 3 and 4 thread starts and the cooling liquid is ammonia.

Preferably also the screw has a LT/De ratio of between 2 and
10 10, more preferably between 2 and 5, even more preferably between 2 and 4.

Preferably also, the extruder is a single screw extruder.

15 It is a fourth object of the invention to provide a process for the manufacturing of frozen food product, wherein a food composition is mixed, aerated and cooled down to a temperature of between -4° and -7° and then processed in an extruder for further cooling down to a temperature of
20 between -12° and -20°, characterised in that the extruder comprises cooling means, the cooling means being preferably constituted by a cooling circuit wherein a cooling liquid is circulated and further comprises an extruding screw having a pitch angle of between 28 and 45 degrees, preferably between
25 32 and 42 degrees, and a LT/De ratio of between 2 and 10, preferably between 2 and 5, more preferably between 2 and 4.

Preferably the cooling liquid is selected within the group
30 consisting of ammonia or nitrogen. Preferably also the screw comprises between 3 and 4 thread starts and the cooling liquid is ammonia.

Detailed description of the invention

The present invention will be further described in the following examples and by reference to the drawing wherein;

5

. Figure 1 represents a schematic view of an extruder comprising an extruding screw.

An ice cream premix having the following composition;

10 Total fat: 8.4%

Stabiliser emulsifier: 0.56%

Added Sugars: 16.8%

Total protein : 3.5%

Total solids: 34.9%

15 Of which Milk solids (non fat): 9.55%

Water: the rest

was aerated up to an overrun of 100% and cooled down to a temperature of -4.5°C using conventional means for subsequent processing.

20

The cooled product obtained was then conveyed to a single screw extruder according to the invention for subsequent extrusion. The product was extruded at 500 litre ice cream per hour in a single screw extruder cooled with ammonia, the screw having a diameter of 200mm.

25

Various screw geometries were tested and the results are summarised in the following table.

Pitch angle (degree)	Channel depth (H) (mm)	Number of Thread Starts	H/Wc	Ice cream temperature (°C)	Torque (Nm)	Ammonia temperature (°C)	Rotation speed (rpm)	Extruder Inlet Pressure (bar)
12	15	2	0.28	-11.6	1572	-30.8	29.0	8
14	17	3	0.43	-11.6	1486	-30.5	30.2	8
19	10	4	0.25	-12.1	1597	-27.2	22.6	8
28	8	4	0.12	-11.9	1629	-27.5	18.8	8
35	8	4	0.10	-12.9	1602	-25.9	14.6	8
40	11	4	0.12	-14.1	1600	-26.8	12.4	8
40	5	6	0.09	-12.2	1609	-25.0	21.0	10
40	7	6	0.12	-12.7	1604	-26.1	20.6	10
40	9.8	6	0.17	-13.7	1602	-26.2	13.2	10
40	11	6	0.19	-13.1	1600	-26.1	12.4	10
40	11	3	0.09	-13.6	1601	-28.2	12.1	10
40	15.5	3	0.12	-13.4	1597	-28.0	10.4	10
40	18	3	0.14	-13.8	1602	-27.6	9.7	10


Claims

1. Extruder comprising an extruding screw, said extruding
5 screw being characterised by between 2 and 6 thread
starts and a pitch angle of between 28 and 45 degrees,
preferably between 32 and 42 degrees.
2. Extruder according to claim 1 comprising cooling means,
10 the cooling means being preferably constituted by a
cooling circuit wherein a cooling liquid is circulated.
3. Extruder according to claim 2 wherein cooling liquid is
15 selected within the group consisting of ammonia or
nitrogen.
4. Extruder according to claim 3 wherein the screw
comprises between 3 and 4 thread starts and the cooling
20 liquid is ammonia.
5. Extruder according to claim 1 wherein the screw LT/De
ratio of between 2 and 10, preferably between 2 and 5,
more preferably between 2 and 4.
- 25 6. Extruder according to claim 1 wherein the H/wc ratio is
under 0.2, preferably over 0.1.
7. Extruder according to any preceding claim wherein the
30 extruder is a single screw extruder.
8. Extruder comprising an extruding screw characterised by
a pitch angle of between 28 and 45 degrees, preferably
32 and 42 degrees, and a LT/De ratio of between 2
and 10, preferably between 2 and 5, more preferably
35 between 2 and 4.

- 10 -

9. Extruder according to claim 8 comprising cooling means, the cooling means being preferably constituted by a cooling circuit wherein a cooling liquid is circulated.
- 5 10. Extruder according to claim 9 wherein the cooling liquid is selected within the group consisting of ammonia or nitrogen.
- 10 11. Extruder according to claim 10 wherein the screw comprises between 3 and 4 thread starts and the cooling liquid is ammonia.
12. Extruder according to any preceding claim 8 to 11 wherein the extruder is a single screw extruder.
- 15 13. Process for the manufacturing of frozen food product, wherein a food composition is mixed, aerated and cooled down to a temperature of between -4° and -7° and then processed in an extruder for further cooling down to a temperature of between -12° and -20° , characterised in that the extruder comprises cooling means, the cooling means being preferably constituted by a cooling circuit wherein a cooling liquid is circulated and further comprises an extruding screw having a pitch angle of
- 20 between 28 and 45 degrees, preferably between 32 and 42 degrees
- 25 14. Process according to claim 13 wherein the screw has a LT/De ratio of between 2 and 10, preferably between 2 and 5, more preferably between 2 and 4.
- 30

Fig.1.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/04724

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A23G9/16 A23G9/04 A23G9/22 A23G9/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23G B29C A23P

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 234 259 A (WIEDMANN WERNER ET AL) 18 November 1980 (1980-11-18) column 2, line 64 -column 6, line 66; claims; figures	1-6,8-11
X	US 5 345 781 A (WINDHAB ERICH ET AL) 13 September 1994 (1994-09-13) cited in the application the whole document	1-3,5,6, 8-10,13, 14
X	WO 99 24236 A (RAUWENDAAL CHRIS J ;RAUWENDAAL EXTRUSION ENGINEERI (US)) 20 May 1999 (1999-05-20) the whole document	1-12
X	EP 0 438 996 A (EURO STEL P V B A) 31 July 1991 (1991-07-31) claims; figures	1,5-8,12
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"8" document member of the same patent family

Date of the actual completion of the international search

6 October 2000

Date of mailing of the international search report

17/10/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Boddaert, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/04724

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 09534 A (UNILEVER PLC ;UNILEVER NV (NL)) 12 March 1998 (1998-03-12) examples ---	1-14
A	US 5 713 209 A (KANOJIA CHAITANYA ET AL) 3 February 1998 (1998-02-03) ---	
A	WO 99 25537 A (DOW CHEMICAL CO) 27 May 1999 (1999-05-27) ---	
A	EP 0 808 577 A (NESTLE SA) 26 November 1997 (1997-11-26) cited in the application ---	
A	WO 97 26800 A (TETRA PAK HOYER A S ;GONON PETER (DK)) 31 July 1997 (1997-07-31) cited in the application ---	
A	US 3 954 366 A (FIELDS REUBEN T) 4 May 1976 (1976-05-04) -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/04724

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4234259 A	18-11-1980	DE 2836940 A	17-04-1980
		ES 483542 D	01-12-1980
		ES 8100954 A	01-03-1981
		FR 2434018 A	21-03-1980
		GB 2028153 A, B	05-03-1980
		IT 1121924 B	23-04-1986
		JP 1457593 C	09-09-1988
		JP 55031495 A	05-03-1980
		JP 63001093 B	11-01-1988
		SU 967268 A	15-10-1982
US 5345781 A	13-09-1994	DE 4202231 C	09-06-1993
		EP 0561118 A	22-09-1993
		US RE36390 E	16-11-1999
		AT 158151 T	15-10-1997
		DK 561118 T	05-01-1998
WO 9924236 A	20-05-1999	US 5932159 A	03-08-1999
		AU 9662298 A	31-05-1999
		EP 1028839 A	23-08-2000
EP 0438996 A	31-07-1991	BE 1003508 A	07-04-1992
WO 9809534 A	12-03-1998	AU 4206797 A	26-03-1998
		AU 4380997 A	26-03-1998
		WO 9809536 A	12-03-1998
		ZA 9707664 A	26-02-1999
		ZA 9708053 A	08-03-1999
US 5713209 A	03-02-1998	AU 5147298 A	15-05-1998
		WO 9817125 A	30-04-1998
WO 9925537 A	27-05-1999	US 6062719 A	16-05-2000
		EP 1032492 A	06-09-2000
EP 0808577 A	26-11-1997	AU 2958797 A	05-01-1998
		BR 9707284 A	20-07-1999
		CA 2223913 A	11-12-1997
		CN 1198076 A	04-11-1998
		WO 9746114 A	11-12-1997
		JP 11509741 T	31-08-1999
		NO 980250 A	13-03-1998
		NZ 329590 A	29-07-1999
WO 9726800 A	31-07-1997	DK 8296 A	23-07-1997
		AU 1437497 A	20-08-1997
		EP 0877558 A	18-11-1998
US 3954366 A	04-05-1976	CA 1049209 A	27-02-1979
		DE 2559068 A	08-07-1976
		FR 2296517 A	30-07-1976
		GB 1515890 A	28-06-1978
		IT 1051166 B	21-04-1981
		JP 1331396 C	14-08-1986
		JP 51092868 A	14-08-1976
		JP 60052924 B	22-11-1985